



# SPECS

**EQUIPMENT SPECIFICATIONS:**  
SIDE REACH 25' 6"  
STOWED TRAVEL HEIGHT 10'  
ARTICULATING ARM TRAVEL: 0 TO 82  
MAIN BOOM TRAVEL: -25 TO 78  
EXTENSION TRAVEL: 110.5"  
NON-PROPORTIONAL CONTROLS  
LOWER CONTROLS WITH OVERRIDE  
ENGINE START/STOP AT PLATFORM  
INDIVIDUAL CONTROL LEVERS  
HYD RATE PRESSURE IS 2200 PSI  
OPERATING PRESSURE IS 2000 PSI  
OPEN CENTER HYDRAULIC SYSTEM  
SHEAR BALL ROTATION DRIVEN  
FULLY ENCLOSED WORM GEAR BOX  
TAIL SHELF WITH WALKUP STEPS



\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

