



SHERMAN+REILLY U1000X PULLER

**IMAGE
COMING
SOON**

SPECS

EQUIPMENT SPECIFICATIONS:

(3) HYD JACKS
3/8 X 2,000' STEEL PULLING CABLE
WHEEL CHOCKS AND HOLDER
SAFETY CHAINS
PULLING CAP 10,000LBS
BULLWHEELS: TWIN CAPSTAN
6 DIA, 5-GROOVE FOLLOWED BY 6-GROOVE
DRIVE SYSTEM HYDRAULIC
22 GAL HYD RESERVOIR
FULL CAP 18 GAL
PULLING ROPE 7/16
6X26 XIP IWRC STEEL WIRE ROPE, 2200FT
BOOM CAMERA: CCD, SWIVEL-MOUNTED AT END OF BOOM
CAB DISPLAY
LEVELWIND: DUAL AUTO FAIRLEAD SHEAVES
SAFE-ZONE CAB
CONTROLS: ALL AT CONTROL PANEL WITHIN CAB: ENGINE& PULLING
DIGITAL INSTRUMENTATION; EMER.STOP; TENSIO METER; VIDEO DISPLAY
WIRELESS CONTROLS: WINCH SPEED & DIRECTION AND EMER.STOP
ELEC SYS 12VDC
45 A ALTERNATOR
US DOT LED 12VDC LIGHTS
FLOOD LIGHTS
BATTERY 12VDC,525CCA
TOOL BOX: STEEL, LOCKABLE, COMPLETE SET OF TOOLS AND E-35D AND E49D CONNECTORS
FIRE EXT ABC
VINYL COVER FOR ROPE DRUM

888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

