



# SHERMAN+REILLY U7500A PULLER

**IMAGE  
COMING  
SOON**

# SPECS

## EQUIPMENT SPECIFICATIONS:

PULLER TRLR MOUNTED S&R  
BULLWHEELS TWIN CAPSTAN  
6 DIA, 5-GROOVE FOLLOWED BY 6-GROOVE  
1ST GEAR 0-60FPM @ 7500LBS  
2ND GEAR: 0-120FPM @ 3500LBS  
REVERSE: 0-300FPM DEMAND PAYOUT  
HYD RESERVOIR 22 GAL  
ENGINE WATER-COOLED  
ELECTRIC START  
FUEL CAP 18GAL  
HYDRAULIC JOYSTICK-CONTROLLED  
3-AXIS, 170 DEG SWING ARC  
80 STORED LENGTH + 30 EXT, BOOM CAMERA: CCD SWIVEL-MOUNTD AT END OF BOOM CAB DISPLAY  
LEVELWIND: DUAL AUTO FAIRLEAD SHEAVES SAFE-ZONE CAB  
FULL ENCLOSURE WITH A/C AND HEAT  
ALL AT CONTROL PANEL WITHIN CAB  
ENGINE & PULLING  
DIGITAL INSTRUMENTATION  
EMER. STOP  
TENSIONMETER  
VIDEO DISPLAY  
WINCH SPEED & DIRECTION AND EMERG STOP 900MHZ ISM BAND  
HYD TOOL CIRCUIT: 7GPM @ 2,000 PSI  
AUX FOR HAND TOOLS  
PUMPS, ETC  
PULLING CONNECTORS: ROTATION-RESISTANT: 1 EA RATED 3,000 LBS & 1 EA RATED 8,000 LB INCLUDED  
STEEL TUBING FRAME CONSTRUCTION  
SUSPENSION LEAF SPRING  
SAFETY CHAINS 2 EACH WITH HOOKS  
FRONT/NOSE JACK HYD  
PART OF AUTO-LEVELING WITH SHOE

888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

