



# STAMM SLT29 SCISSOR LIFT

**IMAGE  
COMING  
SOON**

# SPECS

## **EQUIPMENT SPECIFICATIONS:**

### STAMM SLT29 SCISSOR LIFT 10

THE AERIAL LIFT SHALL CONSIST OF A PLATFORM ATTACHED TO A SCISSOR TYPE LIFT ASSEMBLY, WHICH IS MOUNTED ON THE TRUCK. THE DEVICE SHALL CONFORM TO THE LATEST VERSION OF ANSI/SIA A92.2 AND ALL OTHER APPLICABLE SPECIFICATIONS AND REGULATIONS. THE LIFT SHALL BE THE MANUFACTURER'S LATEST PRODUCTION MODEL AND SHALL BE EQUIPPED WITH STANDARD EQUIPMENT IN ACCORDANCE WITH THE MANUFACTURER'S LATEST DATA. NO PROTOTYPES ARE ALLOWED. THE PLATFORM GROUND TO BOTTOM HEIGHT SHALL BE A MINIMUM 24 FEET, WITH A WORKING HEIGHT OF 29 FEET. THE PLATFORM SHOULD BE CAPABLE OF TRAVERSE MOTION, 60 INCHES TO THE LEFT AND RIGHT WITH A CAPACITY OF 750 POUNDS FULLY EXTENDED. LIFT SHALL HAVE A MINIMUM LOAD CAPACITY OF 1,000 POUNDS. SCISSOR ARMS ARE TO BE CONSTRUCTED FROM 5X2X3/16" ASTM GRADE B TUBING. THE UPPER AND LOWER FRAMES OF THE LIFT SHOULD BE CONSTRUCTED OF 4" STRUCTURAL CHANNEL. ALL PIVOT POINTS ARE TO BE NON-LUBE BUSHINGS WITH A COMPRESSIVE STRENGTH

**888-925-0858**  
**[www.customtruck.com](http://www.customtruck.com)**

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

