



TEREX COMM 5048 DIGGER DERRICK

**IMAGE
COMING
SOON**

SPECS

EQUIPMENT SPECIFICATIONS:

12 48' TEREX COMM 5048
DUAL LIFT CYLINDERS
BOOM INTERLOCK
50 US GALLON HYDRAULIC RESERVOIR
PLANETARY SLIP BRAKE ROTATION
WINCH W/120' OF 7/8 DIA AMSTEEL ROPE W/4 7/8 EYES
SWIVEL HOOK AND 13,320# LOAD CAPACITY
ENGINE START/STOP
THROTTLE ADVANCE & HYDRAULIC TOOL POWER AT PLATFORM
AUGER W/60 LONG X 2-5/8 DIA. HEX DRIVE AUGER SHAFT
HOP, ANTI-TWO BLOCK SYSTEM FOR A 12/24 VOLT SYSTEM
50' HANNAY HOSE REEL W/50' OF HOSE
20,000# PULL WINCHES W/300' OF 1/2 CABLE
6X37 W/EYE, 12 TON SHACKLE
1-FRONT & 1-REAR
VANNER 100 AMP BATTERY EQUALIZER TO CONVERT 24 VOLT SYSTEM TO 12 VOLT
PRECO STROBE LIGHT
3-POINT GROUNDING SYSTEM W/50' OF 2/0 GREEN CABLE
3-RUNG PULL-OUT EZ STEPS

888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

