



# SPECS

## EQUIPMENT SPECIFICATIONS:

PLATFORM LEVELING

LWR CONTROL ON TURNTABLE

BOOM INTERLOCK

ROTATION BEARING IS A HEAVY DUTY SHEAR BALL BEARING W/EXTERNAL GEAR TEETH UTILIZING POLISHED ALLOY STEEL BALLS

FULL PRESSURE OPEN CENTER HYD SYSTEM

20-GAL HYD OIL RESERVOIR

44 PEDESTAL

INSULATED PLATFORM LINER & VINYL PLATFORM COVER

AUX LET DOWN

INSULATED ENGINE STOP/START

PLATFORM REST SADDLE W/A PADDED REST

CHASSIS CONTROLLER

JIB/WINCH INCLUDES UP TO 75' X 3/8 WINCH ROPE & HOOK

CONTROL FOR 1 SET OUTRIGGERS

B/U ALARM

2 OUTRIGGER PADS W/ROPE HANDLE

2 RUBBER WHEEL CHOCKS W/EYE BOLT

GRAB HANDLES AS NECESSARY FOR 3-POINT CONTACT

RIGID STIRRUP STEP MTD ON SIDE ACCESS FOR GROUND TO BODY ACCESS

BRACKET FOR STORING GROUNDING CABLE

2/0 BLACK ELECTRICAL CABLE USED FOR GROUNDING

50' MULTI-STRAND FLEXIBLE COPPER CABLE

3 GROUNDING LUGS

2 FERRULES & GROUNDING CLAMP



888-925-0858

[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

