



TEREX TL-50M

**IMAGE
COMING
SOON**

SPECS

EQUIPMENT SPECIFICATIONS:

END MOUNT PLATFORM

PLATFORM LEVELING

LWR CONTROLS ON TURNTABLE

ENGINE THROTTLE CONTROL AT UPPER CONTROLS

BOOM INTERLOCK

ROTATION BEARING IS A HEAVY DUTY SHEAR BALL BEARING W/EXTERNAL GEAR TEETH UTILIZING POLISHED ALLOY STEEL BALLS

FULL PRESSURE OPEN CENTER HYD SYSTEM

20-GAL HYD OIL RESERVOIR

INSULATED PLATFORM LINER & VINYL PLATFORM COVER

AUX LET DOWN FOR USE W/OPEN CENTER HYDRAULICS

INSULATED ENGINE STOP/START

CHASSIS CONTROLLER

WINCH LEVELS W/PLATFORM (BUT DOES NOT ROTATE W/PLATFORM)

MANUAL ARTICULATION FROM 0 TO 50 DEGREES

MINIMUM REACH OF 49 FROM THE PLATFORM SHAFT

SHEAVE HEAD CAN BE MANUALLY EXTENDED TO 56

JIB W/WINCH IS REMOVABLE & COMES W/SHIP LOOSE SOCKET TO STORE THE JIB/WINCH WHEN REMOVED

JIB INCLUDES 70' OF 1/2 WINCH ROPE & HOOK

CONTROLS FOR 2 SETS OUTRIGGERS & AUX TOOL OUTLETS

B/U ALARM, 4 OUTRIGGER PADS W/ROPE HANDLE

4 RUBBER WHEEL CHOCKS W/EYE BOLT

BRACKET FOR STORING GROUNDING CABLE

888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

