

**IMAGE
COMING
SOON**

SPECS

EQUIPMENT SPECIFICATIONS:

40.8 FT OF HORIZONTAL REACH
POWER ASSIST CONTROL SYSTEM
LOWER BOOM ARTICULATION ENVELOPED IS FROM 0 DEGREES TO 92 DEGREES
UPPER BOOM ARTICULATION OF -35 TO 85 DEGREES
PROVIDES 5 GPM AT 2250 PSI AT ENGINE IDLE
20 GALLON HYDRAULIC OIL RESERVOIR, PEDESTAL & TURNTABLE
60 MESH FILLER SCREEN, BAFFLES
100 MESH SUCTION SCREEN WITH BYPASS
SHUT OFF VALVE, PLATFORM LEVELING
ENGINE THROTTLE CONTROLE
BOOM INTERLOCK
SHEAR BALL ROTATION BEARING
FULL PRESSURE OPEN CENTER HYD SYSTEM
VINYL PLATFORM COVER & LINER
AUXILIARY LET DOWN
TIE DOWN KIT

888-925-0858
www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

