

**IMAGE  
COMING  
SOON**

# SPECS

## EQUIPMENT SPECIFICATIONS:

NON-OVERCENTER, ENGINE TWO SPEED THROTTLE CONTROL  
PLATFORM LEVELING, PLATFORM TILT  
LWR CONTROLS ON TURNTABLE, BOOM INTERLOCK  
PEDESTAL & TURNTABLE  
ROTATION BEARING IS A HD SHEAR BALL BEARING UTILIZING POLISHED ALLOY STEEL BALLS  
3000PSI CLOSED CENTER LOAD SENSING HYD SYSTEM  
70-GAL HYD OIL RESERVOIR  
PLATFORM LINER & VINYL PLATFORM COVER  
ADJ FLOW CONTROL FOR TOOLS  
AUX PWR, FULL ALUMINUM PLATFORM LINER  
120' X 1/2 WINCH LOAD LINE W/SWIVEL HOOK & LATCH  
CONTROLS FOR 2 SETS OUTRIGGERS & AUX TOOL OUTLETS  
B/U ALARM, 4 OUTRIGGER PADS  
4 RUBBER WHEEL CHOCKS W/EYE BOLT  
BRACKET FOR STORING GROUNDING CABLE  
2/0 BLACK ELECTRICAL CABLE USED FOR GROUNDING  
50' MULTI-STRAND FLEXIBLE COPPER CABLE  
3 GROUNDING LUGS  
2 FERRULES & GROUNDING CLAMP  
BOOM REST

888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

