



VERSALIFT VST7500-E100

**IMAGE
COMING
SOON**

SPECS

EQUIPMENT SPECIFICATIONS:

STD PLATFORM CAP 800 BS

PLATFORM CAP W/JIB AND WINCH IS 700 LBS

PLATFORM MOUNTED FULL PRESSURE UNITROL SINGLE-STICK CONTROL INCLUDING SAFETY TRIGGER
EMERGENCY STOP

HYD ARTICULATING DUAL ARM JIB AND WINCH PKG FOR UP TO 1000LBS MAX CAP

ENGINE START/STOP AND 2-SPEED ENGINE THROTTLE CONTROL FROM PLATFORM AND LOWER CONTROLS
CONTINUOUS ROTATION W/3 SLIP RINGS

10GPM OPEN CENTER HYD SYS WITH 3000PSI OPERATING PRESSURE

SIDE MOUNTED TELESCOPE UPPER BOOM ALLOWS LOW STOWING OF PLATFORM
FIBERGLASS INNER BOOM

NON-LUBE BEARINGS USED THROUGHOUT

1 SET OF HYDRAULIC TOOL OUTLETS W/PRESSURE LIMIT 2000PSI AT PLATFORM

QUICK DISCONNECT FITTINGS

RECT PEDESTAL AND FULL LENGTH SUB FRAME W/MAIN AND AUX RADIAL OUTRIGGERS W/PIVOT FEET, K CONTROL VALVES AND A SELECTOR VALVE

INTEGRAL RESERVOIR W/ A 35GAL CAP AND DUAL SIGHT GAUGES

CLOSED HEAVY-DUTY ONE-STEP 24X48X42 FIBERGLASS PLATFORM

EMERGENCY 12V DC HYD SYS, MAIN AND AUXILI

888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

