



# SHERMAN & REILLY PLW-200H HERITAGE PILOT LINE WINDER

2,000 LBS. FOUR DRUM PILOT LINE WINDER





# SPECS

SAFE-ZONE ENCLOSURE WITH OCUVIEW  
REMOTE REEL ENGAGEMENT  
ERGONOMIC HERITAGE CONTROL PANEL WITH  
ADJUSTABLE SEAT  
SUPPORTS RADIO INSTALL, USB AND 12V CHARGING

## FEATURES

2,000 LBS. TOP OF DRUM PULLING CAPACITY  
SUPPORTS THE INSTALLATION OF 4 CONDUCTORS SIMULTANEOUSLY WITH  
LEVELWIND CONTROL OPTION.  
INDEPENDENT ROLLER ASSEMBLIES DESIGNED FOR EACH OF THE FOUR PILOT  
LINES  
SINGLE DRUM CAPACITY: 6,000 FT. OF 7/16 IN. ROPE

## SPECIFICATIONS

MAXIMUM PULLING CAPACITY: 2,000 LBS. RATED AT TOP OF DRUM  
MAX. LINE SPEED: 4 MPH TOP OF DRUM  
REEL CAPACITY: 6,000 FT. OF 7/16 IN. ROPE  
DRIVE SYSTEM: HYDRAULIC MOTOR, CHAIN AND SPROCKET  
ENGINE: KUBOTA TIER 4 DIESEL, 49 PEAK HP, WATER COOLED  
PAYOUT BRAKE: MANUALLY CONTROLLED DISC BRAKES, 12 IN. DIAMETER DISC, BRONZE  
LEVELWIND: HYDRAULICALLY CONTROLLED, JOYSTICK CONTROLLED (2)  
OPERATOR'S SAFETY ENCLOSURE: SAFE-ZONE WITH OCUVIEW OPEN-AIR ENCLOSURE  
LENGTH: 17 FT. 3 IN.  
WIDTH: 102 IN.  
HEIGHT: 109 IN.  
WEIGHT: 10,300 LBS. EST.  
GVWR: 10,800 LBS. EST.  
AXLE CONFIGURATION: SINGLE  
BRAKES (TRAILER): ELECTRIC, WITH SAFETY BREAK-AWAY SWITCH  
BUMPER (R/L) JACKS: (2) MANUAL, DROP AND PIN  
FRONT/NOSE JACK: MANUAL, 2 SPEED HAND CRANK WITH OPTIONAL HYDRAULIC WITH GALVANIZED SHOE (1)  
GROUNDING (4); 3/4 IN. DIA. COPPER-CLAD STEEL LOOPS



888-925-0858  
[www.customtruck.com](http://www.customtruck.com)

\*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

