



SPECS

UTV ACHIEVER RT-02DD

OPEN OR ENCLOSED ROPS CAB

STEERING IS DUAL JOYSTICK CONTROLLED

ENGINE IS DEUTZ TCD 3.6 L4 TIER 4 / 134 HP AT 2,300 RPMS

TRACK IS 29" WITH SOLID RUBBER TIRES

ROTATION IS CONTINUOUS WITH PLANETARY ROTATION DRIVE WITH SLIP BRAKE

40' SHEAVE HEIGHT

BUCKET REACH 47 FT

12,000 FT LB AUGER

4 WAY POLE CLAW

9/16" NYLON ROPE WITH SWIVEL HOOK

AUGER DIGGING RADIUS: 11' TO 19'

LIFTING CAPACITY 6,000 LBS @ 10' RADIUS

FRONT 2 WAY PLOW - OPTION

16,500 LBS ELECTRIC FRONT WINCH - OPTION

HYDRAULIC TOOLS OUTLET IN THE BUCKET - OPTION

JIB 600LB CAPACITY WITH ADJUSTABLE LENGTH AND ANGLE - OPTION

HYDRAULIC TOOL OUTLET ON DECK WITH HOSE REEL WITH TWIN HOSES 3/8" X 30' LENGTH - OPTION

APPROX. WEIGHT = 18,000 LBS

OVERALL LENGTH 220" WITH BOOM IN STORAGE POSITION

OVERALL WIDTH = 101" WITH OUTRIGGERS IN STORAGE POSITION

OVERALL HEIGHT = 118" WITH BOOM IN STORAGE POSITION



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

