



SPECS

PERFORMANCE:

CONTINUOUS LINE PULL RATING OF 4,000 LBS WITH 6,000 FT.; OF 5/8" ROPE ON THE REEL
0-5 MPH PULLING SPEED WITH INFINITE SPEED CONTROL
PULLING AND TENSIONING OPERATIONS ARE COMPLETELY ELECTRICALLY CONTROLLED

REEL CAPACITY:

MAXIMUM REEL DIAMETER 72", WIDTH 56" AND WEIGHT 6,000LBS

REEL SHAFT:

REEL SHAFT IS 2-5/8" IN DIAMETER
SHAFT MOUNTED OVER SPIN BRAKE USING A 16" BRONZE DISC AND
MANUAL CALIPER FOR CONTROLLED PAYOUT OF THE PULLING ROPE IN THE FREEWHEEL MODE

DIMENSIONS:

LENGTH: 16 FT 9 IN
WIDTH: 7 FT 5 IN
HEIGHT: 6 FT 2 IN
WEIGHT: 6,000 LBS

ELECTRIC MOTOR REEL DRIVE:

REEL DRIVE INCORPORATES A SPRING APPLIED-ELECTRIC RELEASED HOLDING BRAKE THAT APPLIES
AUTOMATICALLY IN THE EVENT OF POWER LOSS
FULLY ELECTRIC DRIVE SYSTEM WITH INFINITE SPEED AND TENSION CONTROL
ELECTRIC OVER HYDRAULIC POWERED LEVELWIND WITH A SWING-AWAY TOP OPENING ROLLER
ADJUSTABLE LINE PULL/TENSION CONTROLLER
REEL HOLDING BRAKE CONTROLLER
ELECTRIC, GRAPHICAL COLOR DISPLAY FEATURING:
LINE SPEED, LINE PULL, LINE DISTANCE, PULL IN PAYOUT, AMPS IN/OUT AND STATE OF CHARGE
110 OR 220 VOLT CHARGING SYSTEM - AND RECHARGES WHEN TENSIONING

TRAILER & UNDERCARRIAGE:

TANDEM AXLE SET WITH 14,000 LBS. CAPACITY (15,400 GVWR)



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

