

Extension Arm, 2.5 in X 6 ft

By Chance Lineman Tools & Equipment Catalog # T4032417

EXTENSION ARM 2.5IN X 72IN LONG - 2 WH, The Epoxiglas ™ Extension Arm is designed for use on voltages up to and including 15 kV where reconductoring or insulator replacement is necessary. The Epoxiglas Extension Arm can be used on voltages up to 34.5 kV providing the wireholders are fitted with M4805-7 insulators. The Extension Arm is suspended under the crossarm by brackets to enable to conductor to be removed from the original crossarm and placed in the wireholder mounted on the Epoxiglas Extension Arm.



Features

Extension Arm installed on crossarm. Unit is shown here equipped with M4805-7 insulators on the wireholders. Order insulators separately.

General

Duty Standard Duty

EU RoHS Indicator No
Number of Wireholders 2
Type Arm

UPC 096359059691

Working Load Limit 150 lb Working Load Limit Metric 68 kg

Dimensions

Dimensions 10 in \times 13 in \times 72.5 in

Dimensions Metric 25.4 mm x 33.0 mm x 184.2 mm

72.5 in Height 184.2 mm Height Metric Length 10 in Length Metric 25.4 mm 23 lb Weight WeightMetric 10.4 kg Width 13 in WidthMetric 33 mm

Logistics

Pallet Quantity 96

Product Assets

Installation Manuals - CHANCE® Tools Manuals Sales Drawings - SA_4032417

