

Extension Arm, 2.5 in X 6 ft

By Chance Lineman Tools & Equipment
Catalog # [H480072](#)



EXTENSION ARM, 2.5" X 6', 2 WH, The Epoxiglas™ Extension Arm is designed for use on voltages up to and including 15 kV where reconductoring or insulator replacement is necessary. The Epoxiglas Extension Arm can be used on voltages up to 34.5 kV providing the wireholders are fitted with M4805-7 insulators. The Extension Arm is suspended under the crossarm by brackets to enable the conductor to be removed from the original crossarm and placed in the wireholder mounted on the Epoxiglas Extension Arm.

Features

Extension Arm installed on crossarm. Unit is shown here equipped with M4805-7 insulators on the wireholders. Order insulators separately.

General

Duty	Standard Duty
EU RoHS Indicator	No
Number of Wireholders	2
Type	Arm
UPC	096359040927
Working Load Limit	150 lb
Working Load Limit Metric	68 kg

Dimensions

Dimensions	12 in x 9 in x 73.75 in
Dimensions Metric	30.5 mm x 22.9 mm x 187.3 mm
Height	73.75 in
Height Metric	187.3 mm
Length	12 in
Length Metric	30.5 mm
Weight	21.65 lb
WeightMetric	9.8 kg
Width	9 in
WidthMetric	22.9 mm

Logistics

Pallet Quantity	12
-----------------	----

Product Assets

[Installation Manuals - CHANCE® Tools Manuals](#)
[Sales Drawings - Epoxiglas Extension Arm](#)



A Hubbell brand