

PATRIOT® 4-POINT® 6-Ton Dieless C-Head Battery Actuated Crimper, (2) 3.0Ah 18V Li-ion Batteries, 120V-AC Charger, Hard Case

By Burndy Catalog # PAT4PC834LI

 ${\tt PAT4PC834~4-POINT@~6T~Dieless~C-Head~Battery~Crimper,~3Ah~Li-ion,~AC,~Hard~Case.}$



Features

· Dieless System with range taking capabilities

• 360° head rotation

• 1.06" Jaw opening

· Overmolded handle for comfort and improved grip

• Ergonomically balanced

Application

Crimping

General

Application - For Use On Copper, Aluminum Terminals

and Splices, HYPLUG™

Battery Type 3.0Ah 18V Li-Ion (Accepts

2.0Ah-6.0Ah Makita LI

Batteries)

Catalog Number PAT4PC834LI
Container Type Hard Case
Crimp Force Capacity 6 ton
Die Type Dieless
EU RoHS Indicator Yes

Power Source 120V-AC Charger

Recharge Time 0.5 h

Sub Brand PATRIOT® CRIMPER
Tool Type Battery Actuated Crimper
Trade Name PATRIOT® 4-POINT®

 Type
 Crimper

 UPC
 781810505441

 UPC 12 Digit
 7818105054411

Dimensions

Dimension - Height mm 353.1 mm

Dimensions 15.60 in x 3.20 in x 14.10 in

Height 14.1 in
Length 15.6 in
Weight 12.5 lb
Width 3.2 in

Electrical Ratings

Operating Voltage 18 VDC

Conductor Related

Crimping Ranges Copper Terminals: #8-1000

kcmil

Copper Splices: #8-500 kcmil Copper Flex Terminals: #8-

777.7 Flex

Copper Flex Splices: #8-500

kcmil

Aluminum Terminals: #8-750

kcmil

Aluminum Splices: #8-350

kcmil*

*1.06" barrel diameter

maximum for aluminum splices

due to jaw opening

Aluminum HYPLUG™: #8-750

kcmil

Certifications And Compliance

Buy American Compliant No Standards - RoHS Compliance EX

Status

Logistics

Minimum Pack Quantity 1

Package Contents Crimper, (2) Batteries, Charger,

Lanyard, Hard Case

Product Assets

Catalogs - BURNDY Master Catalog - Section N - Tooling

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

 $Product\ Cross\ Section\ Image(s)\ -\ BUR_PAT4PC834LI_LineArt$

Sales Drawings - 30003020

SDS - Burndy BAT18VLI SDS Sheet (2022-02)

Specifications - PAT4PC834LI



©2024 Hubbell Incorporated. All rights reserved BRDY-PAT4PC834LI-SPEC-EN | REV 10/2024