

# Grip-All 8 ft (2.4 m)

By Chance Lineman Tools & Equipment Catalog # C4030293

GRIPALL - 8FT 7IN. The most versatile tool in a lineworker's hands, the Grip-All stick puts an easy-to-control "finger" on an insulated pole. Although primarily designed for installing hot-line and grounding clamps, it serves both overhead and underground circuits with various end fittings. Commonly called a "shotgun," the operating mechanism incorporates a sliding hand grip that opens the hook to grasp a clamp eyescrew and retract it into the tool head. A thumb latch then must be depressed to release the locked hand grip so it can open the hook. While the tool head is of Lexan® for close-quarter operations, the worker must maintain recommended working distance solely on the Epoxiglas ™ pole section of the handle as the hook and its actuator are metal parts. Easy to care for, Grip-All sticks do not require field stripping to clean. All insulated parts including the operating rod are outside the main pole, readily accessible to wipe dry. CAUTION: Do not clean the plastic head with solvent.

#### **Features**

- External Operating Rod Type
- Tested per OSHA & ASTM F711
- Versatile tool puts an easy-to-control "finger" on an insulated pole
- Primarily designed for installing hot-line and grounding clamps
- Also serves both overhead and underground circuits with various end fittings
- Operating mechanism (or "shotgun") incorporates a sliding hand grip that opens the hook to grasp a clamp eyescrew and retract it into tool head
- Latch must be depressed to release locked hand grip that opens the hook
- For smooth operation, investment-cast stainless-steel components include Jaw, Jaw Holder, Safety Stop, Lockbar and Latch
- Lexan® tool head is designed for close-quarter operations
- Worker must maintain recommended work distance based solely on the Epoxiglas <sup>™</sup> pole section of the handle, as the hook and its actuator are metal parts
- Easy-care Grip-All Clampsticks do not require field stripping to clean
- All insulated parts, including the operating rod, are outside the main pole, readily accessible to wipe dry

## General

Catalog Number C4030293
EU RoHS Indicator No

Storage Bag Included? P643-8 (Bag not included. Must be ordered separately.)

\*Representative Image

Style Standard UPC Standard 096359018100

#### **Dimensions**

Dimension - L Length Overall 2.6 m

mr

Dimension - Length Overall 102 in

inch

Dimensions 107 in x 5 in x 5 in

Dimensions Metric 271.8 mm x 12.7 mm x 12.7 mm

Height 5 in Height Metric 12.7 mm 107 in Length Length Metric 271.8 mm Weight 12 lb WeightMetric 5.4 kg Width 5 in WidthMetric 12.7 mm

#### **Certifications And Compliance**

Buy America(n) Qualified TAA Compliant (All status valid

till December 2024)

## Logistics

Carton Quantity

### **Product Assets**

Catalogs - Insulated Hand Tools

Installation Manuals - CHANCE® Epoxiglas  $^{\text{\tiny TM}}$  Live-Line Tool

Instruction Manual



©2025 Hubbell Incorporated. All rights reserved CLTE-C4030293-SPEC-EN | REV 3/2025