

SLINGCO NON-METALLIC ARAMID CABLE GRIPS FOR PULLING CABLE IN MANY INDUSTRIAL & COMMERCIAL PROJECTS

Slingco has gained a global reputation for innovation. This is shown in our wide range of Non-Metallic Aramid Cable Pulling Grips, which are used in Marine, Utility, Oil & Gas, Construction, Water Treatment, and Mining applications.



Slingco's Non-Metallic Aramid Cable Grip Features:

- Break loads similar to steel cable grips
- Lightweight
- We can create custom grips to meet your specifications
- No More Frayed Grip Wires
- UV Resistant and strong enough to last in salt water, pollutants, and underground

Slingco's line of Non-Metallic Aramid Cable Grips are ideal for use in fiber optic cable installation operations, offshore applications, or for a multitude of uses in the utilities industry.

These grips are made of a high-strength, non-metallic aramid fiber, with UV protective coating, and now feature an improved weight to break ratio. They are suitable for pulling both single cable and multiple cable bundles.

Thanks to the non-metallic material, these grips are easy to work with even without gloves. The woven mesh material also offers a non-metallic, non-conductive alternative to steel grips.

We have many different styles of Non-Metallic Aramid Cable Grips for your project, such as Single Eye, Double Eye, Offset Eye, Lace Up, Mining Grips, and our new Single Eye Double Weave Grips made of ultra flex aramid material. We can also work with you to customize an Aramid Cable Grip to match any particular project specifications.

Call your Slingco Account Manager today and they will help you select the right grip for your project!



FOR ANY INQUIRIES CALL TODAY ON
888 685 9478

Slingco America, Inc. 130 Celtic Blvd, Tyrone, Georgia, 30290, USA
TOLL FREE: 888 685 9478 · Fax: 888 728 4047 · sales@cablegrip.com



www.slingco.com

SINGLE EYE ARAMID CABLE GRIP



SINGLE EYE SINGLE WEAVE NON-METALLIC GRIP

Part No.	Range	Lattice Length	Break Load
ZCS1040	0.38" - 0.75"	24"	2,460 lbs
ZCS1022	0.75" - 1.25"	24"	3,580 lbs
ZCS2923	1.00" - 1.50"	24"	3,580 lbs
ZCS1041	1.25" - 1.50"	24"	4,920 lbs
ZCS1042	1.50" - 2.00"	24"	5,820 lbs

SINGLE EYE DOUBLE WEAVE NON-METALLIC GRIP

Part No.	Range	Lattice Length	Break Load
ZCS1023	1.25" - 1.50"	24"	9,860 lbs
ZCS1024	1.50" - 2.00"	24"	11,880 lbs
ZCS1179	2.00" - 2.50"	24"	15,900 lbs
ZCS1180	2.50" - 3.00"	24"	15,900 lbs
ZCS1181	3.00" - 4.00"	24"	15,900 lbs
ZCS4079	4.00" - 5.00"	120"	15,900 lbs

DOUBLE EYE ARAMID CABLE GRIP



DOUBLE EYE SINGLE WEAVE NON-METALLIC GRIP

Part No.	Range	Lattice Length	Break Load
ZCS1148	0.38" - 0.75"	24"	2,460 lbs
ZCS1176	0.75" - 1.25"	24"	3,580 lbs
ZCS2922	1.00" - 1.50"	24"	3,580 lbs
ZCS1177	1.25" - 1.50"	24"	4,920 lbs
ZCS1178	1.50" - 2.00"	24"	5,820 lbs

DOUBLE EYE DOUBLE WEAVE NON-METALLIC GRIP

Part No.	Range	Lattice Length	Break Load
ZCS1182	1.25" - 1.50"	24"	9,860 lbs
ZCS1183	1.50" - 2.00"	24"	11,880 lbs
ZCS1184	2.00" - 2.50"	24"	15,900 lbs
ZCS1185	2.50" - 3.00"	24"	15,900 lbs
ZCS1186	3.00" - 4.00"	24"	15,900 lbs
ZCS3813	4.00" - 5.00"	60.6"	15,900 lbs

OFFSET EYE ARAMID GRIP



SINGLE OFFSET EYE SINGLE WEAVE NON-METALLIC GRIP

Part No.	Range	Lattice Length	Break Load
ZCS2810	0.38" - 0.75"	24"	2,460 lbs
ZCS2811	0.75" - 1.25"	24"	3,580 lbs
ZCS2921	1.00" - 1.50"	24"	3,580 lbs
ZCS2812	1.25" - 1.50"	24"	4,920 lbs
ZCS2813	1.50" - 2.00"	24"	5,820 lbs

SINGLE OFFSET EYE DOUBLE WEAVE NON-METALLIC GRIP

Part No.	Range	Lattice Length	Break Load
ZCS2814	1.25" - 1.50"	24"	9,860 lbs
ZCS2815	1.50" - 2.00"	24"	11,880 lbs
ZCS2816	2.00" - 2.50"	24"	15,900 lbs
ZCS2817	2.50" - 3.00"	24"	15,900 lbs
ZCS2818	3.00" - 4.00"	24"	15,900 lbs

SINGLE OFFSET EYE LACE UP ARAMID GRIP



SINGLE OFFSET EYE LACE UP NON-METALLIC ARAMID GRIP

Part No.	Range	Lattice Length	Break Load
ZCS09323	0.622" - 1.00"	59"	13,000 lbs

SINGLE EYE DOUBLE WEAVE ARAMID GRIP



SINGLE EYE DOUBLE WEAVE NON-METALLIC GRIP

Part No.	Range	Color Code	Break Load
ZCS09336	0.63" - 0.75"	Yellow	5,000 lbs
ZCS09337	0.75" - 1.00"	Red	6,000 lbs
ZCS09338	1.00" - 1.25"	Blue	6,000 lbs
ZCS09339	1.25" - 1.50"	White	6,000 lbs

DOUBLE OFFSET EYE ARAMID GRIP



DOUBLE OFFSET EYE DOUBLE WEAVE NON-METALLIC GRIP

Part No.	Range	Lattice Length	Break Load
ZCS6823	3.00" - 4.00"	33.5"	9,000 lbs