# MANUAL CRIMPER

## **A WARNING**

Cancer and Reproductive Harm: www.P65Warnings.ca.gov



### **KEY FEATURES**

- ✓ 'D3' groove allows 'W' style die inserts for installing taps, splices, and terminal connectors
- Kearney Seat Tool accepts Kearney type dies
- Ergonomic handles for comfortable use and maximum leverage

Slingco's Mechanical Crimping Tools have been created to complete the variety of utility distribution service connections that need to be made on the line, pole, and home. Our crimping tools have been designed to provide reliable crimps installing full-tension or non-tension connectors.

Slingco's Mechanical Crimping Tool's 'D3' groove allows 'W' style die inserts for installing taps, splices, and terminal connectors. The 'W' die inserts lock securely and easily into place with the positive lock, spring-loaded die buttons. Slingco also offers a Mechanical Crimping Tool that accepts Kearney type dies.

Our Mechanical Crimping Tools also have ergonomic handles for comfortable use and maximum leverage when making critical connections.

Slingco Part No.	Tool Type	Crimp Force (lb)	Length (in)	Weight (lb)
TCR7002	0&D	9,000	25.75	7
TCR7004	BG&D	9,000	25.75	7
TCR08735	5/8 Nose Die & Kearney Seat (Accepts 'Kearney' type)	9,000	25.75	7





**GET IN TOUCH** 



1 888 685 9478 sales@slingcoamerica.com

# MANUAL CRIMPER

Slingco Part No.	Slingco Ref.	Burndy Equiv.
TCR7020	S6-K840	WK840
TCR7021	S6-BG	WBG
TCR7022	S6-O	WO
TCR7023	S6-247	W247
TCR7024	S6-249	W249
TCR7025	S6-121	W121
TCR7027	S6-163	W163
TCR7028	S6-164	W164
TCR7029	S6-165	W165
TCR7030	S6-166	W166
TCR7031	S6-167	W167
TCR7034	S6-237	W237
TCR7036	S6-239	W239
TCR7037	S6-241	W241
TCR7038	S6-243	W243
TCR7039	S6-245	W245
TCR7047	S6-C	WC
TCR7058	S6-25RT	W25RT
TCR7059	S6-26RT	W26RT

CI: D IN	C. D. C	r, B. C.
Slingco Part No.	Slingco Ref.	Kearney Die Size
TCR10117	0 Die - 1/2	1/2
TCR10118	O Die - 1/4	1/4
TCR10119	O Die - 3/8	3/8
TCR10120	0 Die - 5/8-1	5/8-1
TCR10121	O Die - 5/16	5/16
TCR10122	O Die - 9/16	9/16
TCR10123	O Die - 11/16	11/16
TCR10124	O Die - 19/32	19/32
TCR10125	O Die - 620	620
TCR10126	O Die - 635	635
TCR10127	O Die - 747	747
TCR10128	0 Die - 781	781
TCR10129	0 Die - 840	840
TCR10130	O Die - 845	845
TCR10131	O Die - B	В
TCR10132	O Die - 3/16	3/16
TCR10133	O Die - T	Т
TCR10134	O Die - D	D
TCR10135	O Die - J	J
TCR10136	O Die - K	К
TCR10137	0 Die - 0	0
TCR10138	O Die - P	Р
TCR10139	0 Die - 737	737





## **GET IN TOUCH**



1 888 685 9478 sales@slingcoamerica.com

# MANUAL CRIMPER

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco America, Inc.

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-5%. Please contact us if you have any questions.

**Range dimension overlaps** If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.





**GET IN TOUCH** 



18886859478

