

## Duckbill Ground Clamp, Type I- Class A-Grade 5 & 3H, 1.162 in Jaw Opening

By CHANCE Lineman Grade Tools

Catalog # [C6001734](#)



Duckbill Ground Clamp, Type I-Class A-Grade 5 & 3H, 1.162" Jaw  
Opening

### Features

- Duckbill Ground Clamp
- Continuous Current 400A
- Fault Current Grade 3H - 31kA 15 cycles X/R=30 or Grade 5 - 43kA for 15 cycles or 30kA for 30 cycles
- Main Line Range Max. 566kcmil CU or 900kcmil ACSR (1.162"),
- Main Line Range Min. #6 Sol. CU (0.162")
- Jumper Range Max. 4/0 Grd. Cable
- Jumper Range Min. #2 Grd. Cable
- ASTM Type I, Class A, Grade 3H or Grade 5
- IEC Rating 35kA (15 cycles)
- Jaws Smooth
- Ferrule Threaded

### General

Catalog Number	C6001734
Eye Screw/T-Handle	250 in-lb
Installation Torque (in-lb)	
Ferrule Installation Torque (in-lb)	250 in-lb
Handle Type	Eyescrew
Jaw Type	Smooth Jaws
Material	Aluminum
Terminal Connection Type	5/8"-11 Thread
Thread Size	5/8-11 UNC
Thread Type	Threaded
Torque Rating	250 in-lbs
UPC	096359023876

### Dimensions

Dimensions	3.81 in x 6.3 in x 2.23 in
Height	2.23 in
Jaw Opening Size - Maximum	1.162 in
Jaw Opening Size - Minimum	.162 in
Length	3.81 in
Weight	1.372 lb
Width	6.3 in

### Electrical Ratings

Current Rating	400 A
Fault Current - 15 Cycles	43000 A
Fault Current - 30 Cycles	30000 A
Grounding Wire Capacity Maximum	4/0 Cable w/ Threaded Terminal
Grounding Wire Capacity Minimum	#2 Cable w/ Threaded Terminal

### Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
Fault Current - ASTM Grade IEC Compliant	Grade 5 35 kA

### Logistics

Pallet Quantity	750
-----------------	-----

### Product Assets

<a href="#">Catalogs - Grounding Equipment</a>
<a href="#">Sales Drawings - Grounding Clamp (SA6001734)</a>
<a href="#">Specifications - C6001734</a>