

C-HEAD GROUND CLAMPS



	CAT NO	DESCRIPTION	CLAMPS WITH 5H RATING*	MAIN LINE RANGE MAXIMUM MINIMUM	MAXIMUM SIZE CABLE	MAXIMUM FAULT CURRENT RATING	TERMINAL TYPE	LBS
BRONZE	21070	SERRATED JAW	*5H RATED	2.88 O.D. CABLE OR BUS 6 SOLID .16” DIA	4/0	43KA@ 15 CYCLES 30KA@ 30 CYCLES	THREADED	3.3
	21552	SERRATED JAW		500 MCM .813 DIA 8 SOLID .128 DIA				1.4
	21307	SERRATED JAW	*5H RATED	1.033 MCM ACSR 1.25 DIA 6 SOLID .16 DIA				2.3
ALUMINUM	21575	SERRATED JAW	*5H RATED	1.50” DIA CABLE OR BUS 6 SOLID .16 DIA	4/0	43KA@ 15 CYCLES 30KA@ 30 CYCLES	THREADED	1.5
	10375	SERRATED JAW	*5H RATED	2” DIA CABLE OR BUS 4 SOLID .18 DIA				1.8
	10376	SAME AS 10375 BUT WITH SMOOTH UPPER JAW						1.8
	11190	SERRATED JAW		1.0335 MCM ACSR 1.5 DIA 8 SOLID .12 DIA			BOLTED	1.3
	11192	SAME AS 11190 BUT WITH SMOOTH UPPER JAW		1.0335 MCM ACSR 1.25 DIA 8 SOLID .12 DIA				1.3
	3172	SMOOTH JAW		2” DIA CABLE OR BUS 6 SOLID .16 DIA				2.4

5H RATED GROUND SETS (See Above)*

HASTINGS 5H Rated Ground Sets require all components (Clamps, 4/0 Cable, Ferrules, Etc.) to be manufactured and assembled by HASTINGS.

HASTINGS strictly will not recognize or approve a 5H Rating for any Ground Set(s) that are not manufactured and assembled by HASTINGS.